

DESCRIPTION

Angle Seat Valve - 2/2 NC - Inlet Under Seat

PRESENTATION

- Compact solution
- Maintenance free sealing pack
- NPT thread on request
- AISI 316 body available on request
- From 3/8" up to 2"
- 3/4" and 1 1/4" version available on request


USE: Food, Packaging, Petrochemical, Metallurgical, Spraying, Vehicles, Printing and Dyeing Machinery equipment

CONNECTION: Threaded (BSP, BSPT,NPT)



VALVE FEATURES

Fluid Pressure	Max 16bar (232psi)
Control Pressure	3 - 8bar (43.5 - 116psi)
Control Fluid	Neutral gases, Air
Body material	AISI 304
Sealing	PTFE
Fluids	Water, Oils, Gases, Pulp and other liquids
Fluid viscosity	Max 600cSt (mm ² /s)
Fluid temperature	-10°C to +120°C
Ambient temperature	-10°C to +80°C
Control Type	Double acting



OVERALL DIMENSION

CODE	Actuator	ND mm	Pilot Pressure bar	Max Pressure bar	G	N mm	K mm	C mm	T mm	A mm	L mm	SW mm
PEE332CGW10/V	32	ND10	3 - 8	16	3/8"	5	99	37	12	112	68	27
PEE332DGW15/V	32	ND15	3 - 8	16	1/2"	5	93	37	15	105	68	27
PEE340FGW25/V	40	ND25	3 - 8	16	1"	5	108	45	17	22	90	40
PEE350HGW40/V	50	ND40	3 - 8	16	1 1/2"	5	154	55	21	68	116	56
PEE363IGW50/V	63	ND50	3 - 8	16	2"	5	154	69	22	78	138	69

